



Fixture Library		
Quad Par (7ch) 伊東洋行 : itoyoko-LED Quad Par (7DMX) ([d----] Mode)		
Color Source For(6ch) ETC : ETC -ColorSource Linear1 Deep Blue Direct (6DMX) ([dir] - Mode)		
LH-LED (8ch) PHILIPS : SL eSTRIP10 RGBW (8 DMX) ([1pixel]-[16bit] Mode) (Line(1) =Dimmer Ch-461~468)		
2L Mini (1ch) CH-1 Dimmer	6L Mini (1ch) CH-1 Dimmer	Cobla (1ch) CH-1 Dimmer

フロア用 移動器材 アドレス	
351	358
365	372
379	
473	479
485	
M/B (600m/m 吊)	Smork(Antari)
505(Speed) 506(正逆)	511(Fog)512(Int.Fan)
501	LH-LED (Dim) (SL eSTRIP 10)
502	客席 LED (Dim) (天井当て)
503	461 (R)
504	462 (W)
	463 (G)
	464 (R)
	465 (B)
	466 (W)
	467 (W)
	468 (W)
	496 (W)
	497 (W)
	498 (R)
	499 (G)
	500 (B)

ALL LED!

赤字 Line ① } 設定済み
青字 Line ② } アドレス変更、要注意

持込器材用 [Line ③
Line ④



- CL固定 (天井裏) 当替え不可
- : Quad PAR (LED)
 - : Source Four (LED)
 - : COBLA (作業灯用) (LED)

2024/03/10 更新

HULIC ヒューリックホール東京・照明 Hall Fader配線図 (配布用) S- = 1/50 (A3)